2026 Ford Mustang Dark Horse® SC

TECHNICAL SPECIFICATIONS

09/22/26 v 1.0



Preproduction vehicle shown with additional features. Actual vehicle production may vary.

BODY INFORMATION

Body style	Fastback (widebody)
Body material	Unitized welded steel body, aluminum hood and steel front fenders
Chassis	Fully independent front/rear suspension and perimeter subframe
Trim levels	Mustang Dark Horse SC, Dark Horse SC Track Pack, Dark Horse SC Track Pack Special Edition
Final assembly location	Flat Rock Assembly Plant, Flat Rock, Michigan

DRIVETRAIN

Standard	Front-engine, rear-wheel drive, limited-slip differential

ENGINE SPECS AND KEY FEATURES

	5.2L Supercharged V8
Horsepower(1) (@ rpm)	795 @ 7,200
Torque(1) (lb.-ft. @ rpm)	660 @ 4,600
Configuration	90-degree V8, forged steel cross-plane crankshaft
Induction	Intercooled supercharger
Engine Block Material	Aluminum
Cylinder Head Material	Aluminum
Displacement (liters)	5.2
Bore x Stroke (inches/mm)	3.70 x 3.66/94 x 93
Compression Ratio (:1)	9.5
Valvetrain	DOHC, 24 valve
Ignition System	Distributor-less with coil-on-plug
Fuel Delivery	Port fuel injection
Engine Control System	Powertrain control module

(1) Horsepower and torque ratings are based on premium fuel per SAE J1349® standard. Your results may vary. When properly equipped. Horsepower and torque ratings are independent attributes and may not be achieved simultaneously.

TRANSMISSION

Standard 7-speed TREMEC® dual-clutch automatic with carbon fiber driveshaft

	Gear Ratios (:1)
First	3.14
Second	2.05
Third	1.43
Fourth	1.10
Fifth	0.86
Sixth	0.68
Seventh	0.56
Final Drive, Differential Type	3.73 TORSEN® limited-slip rear axle

NOTE: TREMEC is a registered trademark of KUO S.A. DE C.V.
NOTE: TORSEN is a registered trademark of JTEKT Corporation.

SUSPENSION

Type Fully independent front/rear, perimeter subframe, magnesium tower-to-tower brace

Front Configuration	Double-ball-joint MacPherson strut with stabilizer bar and aluminum control arms with MagneRide® dampers
Front Shock Absorbers	MagneRide
Front Stabilizer Bar Type	Hollow
Front Stabilizer Bar Diameter (mm)	36.0 x 5.4 (Base) 36.0 x 5.7 (Track Pack, Track Pack Special Edition)
Rear Configuration	Integral-link independent with coil springs and stabilizer bar with MagneRide dampers
Rear Shock Absorbers	MagneRide
Rear Stabilizer Bar Type	Hollow
Rear Stabilizer Bar Diameter (mm)	24.2 (Base) 25.4 (Track Pack, Track Pack Special Edition)

NOTE: MagneRide is a trademark of BWI Company Limited S.A.

STEERING

Type Electric power-assisted steering (EPAS) with Selectable-Effort

Steering Modes	Normal, Comfort, Sport
Steering Ratio	16.0:1

BRAKES

Type 4-wheel disc with Anti-Lock Brake System (ABS) and AdvanceTrac®

Front		
Rotor Size (diameter x thickness; mm)		420 x 40
Caliper Type	**Iron System (standard)**	Two-piece directional-vane iron rotor; staggered 6-piston fixed-bridge aluminum monobloc Brembo® caliper
	Carbon Ceramic System (available)	Two-piece directional-vane carbon ceramic rotor; staggered 6-piston fixed-bridge aluminum monobloc Brembo caliper with electronic pad wear sensors
Pad Material		Low-metallic compound (iron system) High-performance linings (carbon ceramic system)
Rear		
Rotor Size (diameter x thickness; mm)		370 x 30
Caliper Type	**Iron System (standard)**	two-piece iron rotor; staggered 4-piston aluminum monobloc Brembo caliper
	Carbon Ceramic System (available)	two-piece directional-vane carbon ceramic rotor; staggered 4-piston aluminum monobloc Brembo caliper
Pad Material		Low-metallic compound (iron system) High-performance linings (carbon ceramic system)

NOTE: Brembo is a trademark of Brembo S.p.A.

EXTERIOR DIMENSIONS (inches unless otherwise noted)

Wheelbase	107.0
Overall Length	190.6
Width (without mirrors)	76.5
Overall Height (with Track Pack)	53.7
Track Width — Front	64.0
Track Width — Rear	64.5

INTERIOR DIMENSIONS (inches unless otherwise noted)

Seating Capacity 4 (Base)
2 (Track Pack, Track Pack SE)

Front Head Room	37.6
Front Leg Room (SAE max.)	44.5
Front Shoulder Room	56.3
Front Hip Room	54.9
Rear Head Room (4-seater)	34.8
Rear Leg Room (SAE max., 4-seater)	29.0
Rear Shoulder Room (4-seater)	52.2
Rear Hip Room (4-seater)	47.4
Passenger Volume (cu. ft., 4-seater)	82.8
Trunk Volume (cu. ft.)	13.3

CURB WEIGHTS (pounds unless otherwise noted)

Base	4,263
Track Pack	4,110

WHEELS

Mustang Dark Horse SC Base	Track Pack/Track Pack Special Edition
20" x 11" aluminum — 26 mm offset (front) 20" x 11" aluminum — 43 mm offset (rear)	20" x 11.5" carbon fiber — 25 mm offset (front) 20" x 11.5" carbon fiber — 46 mm offset (rear)

TIRES

Mustang Dark Horse SC Base	Track Pack/Track Pack Special Edition
305/30ZR20 Pirelli® P Zero R	305/30ZR20 Michelin® Pilot® Sport Cup 2 R

NOTE: **Pirelli** is a registered trademark of Pirelli & C.S.P.A.

NOTE: **Michelin** is a registered trademark of Michelin North America, Inc.

WARRANTY

Bumper-to-Bumper	3 years/36,000 miles
Powertrain	5 years/60,000 miles
Aluminum Body Panels	5 years/unlimited miles
Corrosion Sheet Metal (perforation only; excludes aluminum)	5 years/unlimited miles
Paint Adhesion	5 years/unlimited miles
Roadside Assistance	5 years/60,000 miles