

2026 Ford Ranger® Pickup

TECHNICAL SPECIFICATIONS

01/13/26 V1.0



NOTE: Always consult the Owner's Manual before off-road driving, know your terrain and trail difficulty, and use appropriate safety gear

BODY INFORMATION

Body style	Body on frame, SuperCrew®
Frame construction	Fully boxed, high-strength steel
Body material	Mild steel and aluminum body panels
Trim levels	XL, XLT, Lariat®, Raptor®
Final assembly location	Michigan Assembly Plant, Wayne, Michigan

DRIVETRAIN

Standard	Front engine, rear-wheel drive (4x2) with open differential rear axle (XL, XLT, Lariat)
	Advanced 4x4 with automatic on-demand engagement (Raptor only)
Optional	Front engine, electronic shift-on-the-fly 4x4 transfer case with open differential (XL, XLT, Lariat)
	Front engine, electronic shift-on-the-fly 4x4 transfer case with electronic-locking rear differential (XL, XLT, Lariat)

ENGINE SPECS AND KEY FEATURES

	2.3L EcoBoost® I-4	2.7L EcoBoost V6	3.0L EcoBoost V6
Horsepower ⁽¹⁾ (@ rpm)	270 @ 5,500	315 @ 5,000	405 @ 5,750 ⁽²⁾
Torque ⁽¹⁾ (lb.-ft. @ rpm)	310 @ 3,000	400 @ 3,000	430 @ 4,500 ⁽²⁾
Available Maximum Conventional Towing ⁽³⁾ (lbs.)	7,500	7,500	5,510
Available Maximum 4x4 Payload ⁽⁴⁾ (lbs.)	1,763	1,513	1,373
Configuration	Inline 4-cylinder, dual overhead cam	60-degree V6, dual overhead cam	60-degree V6, dual overhead cam
Induction	Single twin-scroll turbocharger	Twin turbocharged/intercooled	Twin turbocharged/intercooled
Engine Block Material	Aluminum	Compacted graphite iron	Aluminum
Cylinder Head Material	Aluminum	Aluminum	Aluminum
Displacement (liters/cubic inches)	2.3/140	2.7/165	3.0/180
Main Bearings	6	4	4
Bore x Stroke (inches)	3.45 x 3.70	3.27 x 3.27	3.36 x 3.39
Compression Ratio (:1)	10.0	10.0	10.5
Valvetrain	Roller finger follower	Roller finger follower	Roller finger follower
Ignition System	Coil-on-plug	Coil-on-plug	Coil-on-plug
Fuel Delivery	Direct injection	Port fuel and direct injection (PFDI)	Direct injection
Recommended Unleaded Fuel (minimum)	Regular 87 octane	Regular 87 octane	Premium 91+ octane
Oil Capacity, Including Filter (quarts/liters)	5.6/5.3	6.0/5.7	7.0/6.6
Coolant Capacity (quarts/liters)	10.5/9.9	12.4/11.7	12.4/11.7

(1) When properly equipped. Maximum horsepower, torque, payload and towing are independent attributes and may not be achieved simultaneously.

(2) Horsepower and torque ratings are based on premium fuel per SAE J1349® standard. Your results may vary.

(3) When properly equipped. Maximum towing varies based on cargo, vehicle configuration, accessories, and number of passengers.

(4) Maximum payload varies and is based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.

TRANSMISSION

Standard 10-Speed SelectShift® electronically controlled automatic

Gear	Ratio (:1)
First	4.71
Second	3.00
Third	2.15
Fourth	1.77
Fifth	1.52
Sixth	1.28
Seventh	1.00
Eighth	0.85
Ninth	0.69
Tenth	0.64
Reverse	4.89

TRANSFER CASE

Type 2-speed with planetary gears

	Electronic shift-on-the-fly (XL, XLT, Lariat)	Advanced 4x4 with automatic on-demand engagement (Raptor only)
Gear Ratio – Low	1.00:1	1.00:1
Gear Ratio – High	2.72:1	3.06:1
Maximum Crawl Ratio	Not Available	67.88:1
Lubricant Capacity (quarts/liters)	1.3/1.2	1.6/1.55
Case Material	Aluminum	Aluminum

SUSPENSION

	XL, XLT, Lariat	Raptor
Front Configuration	Short- and long-arm independent and tubular stabilizer bar	Short- and long-arm independent with forged aluminum A-arms
Front Shock Absorbers	Gas-pressurized	Coil-overs spring, gas-pressurized 2.5" FOX™ Internal Bypass with Live Valve™ Technology
Rear Configuration	Hotchkiss-type, non-independent live axle with leaf springs and outboard shock absorbers	Watts-link rear suspension with trailing arms
Rear Shock Absorbers	Gas-pressurized	Gas-pressurized FOX Internal Bypass with piggyback resevoirs and Live Valve Technology

CREDIT LINE: FOX is a trademark of FOX Factory, Inc.

STEERING

Type Electronic power-assisted

	Wheelbase (inches)	Steering Ratio (:1)	Turning Diameter (feet, curb-to-curb)
XL, XLT, Lariat	128.7	17.6	42.0
Raptor	128.7	17.4	43.3

BRAKES

Type Power-vented disc with Anti-Lock Brake System (ABS) and Automatic Emergency Braking (AEB)

	XL, XLT, Lariat	Raptor
Front Specifications		
Rotor Size (diameter x thickness; mm)	311 x 34	341 x 34
Swept Area (sq. cm)	415.0	534.7
Caliper Type	Floating caliper, dual-piston	Floating caliper, dual-piston
Piston Diameter (mm)	51	51
Rear Specifications		
Rotor Size (diameter x thickness; mm)	308 x 24	332 x 24
Swept Area (sq. mm)	374.8	378.5
Caliper Type (includes electric integrated parking/emergency brake)	Floating caliper, single-piston	Floating caliper, single-piston
Piston Diameter (mm)	54	54
Electric Parking Brake Rating (kN)	25.5	25.5

FUEL TANK CAPACITY

Engine	Fuel Tank Capacity (gallons)
2.3L EcoBoost I-4 and 2.7L EcoBoost V6	18.7
3.0L V6 (Raptor only)	20.3

EXTERIOR DIMENSIONS (inches unless otherwise noted)

	4x2	4x4	Raptor 4x4
Wheelbase	128.7	128.7	128.7
Overall Length	210.6	210.6	210.9
Vehicle Height (maximum)	74.4	74.4	75.9
Width (excluding mirrors)	75.5	75.5	79.8
Width (including mirrors)	86.7	86.7	86.7
Width (mirrors folded)	79.0	79.0	79.0
Track Width – Front	63.8	63.8	67.3
Track Width – Rear	63.8	63.8	67.3
Overhang – Front	34.1	34.1	33.9
Overhang – Rear	47.8	47.8	48.2
Angle of Approach	30.2°	30.2°	33.0°
Ramp Breakover Angle	23.0°	23.0°	24.2°
Angle of Departure	25.8°	25.8°	26.4°
Ground Clearance	9.3	9.3	10.7
Open Tailgate to Ground (empty)	34.7	34.7	36.1
Front Bumper to Back of Cab	143.2	143.2	143.2

INTERIOR DIMENSIONS (inches unless otherwise noted)

	SuperCrew
Seating	5
Front Head Room (SAE max.)	41.0
Front Leg Room (SAE max.)	43.2
Front Shoulder Room	57.1
Front Hip Room	55.9
Rear Head Room	38.3
Rear Leg Room	34.6
Rear Shoulder Room	56.7
Rear Hip Room	54.1
Front Passenger Volume (cu. ft.)	54.7
Rear Passenger Volume (cu. ft.)	43.5
Total Passenger Volume (cu. ft.)	98.3
Cargo Volume Behind First Row (rear-seat back folded; cu. ft)	33.9

CARGO CAPACITIES (inches unless otherwise noted)

	4.97-ft. Box
Inside Length at Floor	59.6
Length at Top	57.9
Width Between Wheelhouses	48.2
Opening Width at Floor	53.7
Opening Width at Top	55.6
Maximum Inside Width	62.4
Inside Height at Molding	20.8
Cargo Box Volume (cu. ft.)	43.5

WEIGHTS (pounds)

	2.3L EcoBoost I-4		2.7L EcoBoost V6	3.0L EcoBoost V6 (Raptor)
	4x2	4x4	4x4	4x4
Base Curb Weight	4,240	4,462	4,610	5,363
Gross Vehicle Weight Rating (GVWR)	6,050	6,270	6,170	6,790
Gross Combination Weight Rating (GCWR)	12,370	12,590	12,745	11,465
Maximum Payload ⁽¹⁾	1,767	1,763	1,513	1,373
Maximum Towing ⁽²⁾	7,500	7,500	7,500	5,510

(1) Maximum payload varies and is based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle.

Always properly secure cargo.

(2) When properly equipped. Maximum towing varies based on cargo, vehicle configuration, accessories, and number of passengers.

WHEELS

Standard	Optional
17" black-painted steel (XL)	17" silver-painted aluminum (XL)
17" gray-painted aluminum (XLT)	17" forged-aluminum, beadlock-capable (Raptor)
17" gray-painted aluminum (Raptor)	18" black-painted aluminum (Black Appearance Package)
18" machined-aluminum with dark-painted pockets (Lariat)	18" chrome-like PVD aluminum (Chrome Appearance Package)

TIRES

Standard	Optional
255/70R17 all-terrain (XL, XLT)	LT255/70R17 all-terrain OWL (XLT with FX4® Off-Road Package only)
255/65R18 all-terrain (Lariat)	
LT285/70R17 all-terrain (Raptor)	

WARRANTY

Bumper-to-bumper

3 years/36,000 miles

Powertrain

5 years/60,000 miles

Aluminum body panels

5 years/unlimited miles

Corrosion sheet metal (perforation only excludes aluminum)

5 years/unlimited miles

Paint adhesion

5 years/unlimited miles

Roadside assistance

5 years/60,000 miles