

2026 FORD TRANSIT®

TECHNICAL SPECIFICATIONS



BODY

Construction/materials	Steel unibody
Trim levels	Cargo Van, Passenger Van (XL/XLT), Chassis Cab, Cutaway
Roof options	Low, Medium, High
Wheelbase lengths	130" and 148" Cargo Van; 148" Passenger Van; 138", 156", and 178" Chassis Cab/Cutaway Regular, Long, Extended length
Final assembly location	Kansas City Assembly Plant, Kansas City, MO ¹

DRIVETRAIN

Standard layout	Front engine, rear-wheel drive (RWD)
Optional layout	Front engine, all-wheel drive (AWD)

ENGINES

	3.5L PFDI V6 engine	3.5L EcoBoost® V6 engine
Configuration	Naturally-aspirated V6, overhead cams	Twin-turbocharged and intercooled V6, overhead cams
Block/head material	Aluminum block, aluminum heads	Aluminum block, aluminum heads
Displacement	3.5 liters (213 cubic inches)	3.5 liters (213 cubic inches)
Bore x stroke	3.64 inches x 3.41 inches	3.64 inches x 3.41 inches
Compression ratio	11.8:1	10.0:1
Valvetrain	Double overhead cam, direct acting mechanical bucket, 24 valves	Double overhead cam, direct acting mechanical bucket, 24 valves
Ignition system	Coil-on plug (COP)	Coil-on plug (COP)
Fuel delivery	Port Fuel Direct-Injection (PFDI)	Gasoline Turbocharged Direct Injection (GTDI)
Recommended fuel	Regular Unleaded or E85 (87 octane minimum)	Regular Unleaded or E85 (87 octane minimum)
Engine control system	Electronic	Electronic
Oil capacity/grade	6 quarts	6 quarts
Coolant capacity	14.25 liters (15.1 qt.)	14.1 liters (14.9 qt), 15.5 liters (16.4 qt) with auxiliary heater
SAE horsepower	275 hp @ 6,250 rpm	300 hp @ 5,000 rpm
SAE torque	260 ft-lbs @ 4,000 rpm	400 ft-lbs @ 2,500 rpm

¹Assembled in the USA with domestic and foreign parts.



ELECTRICAL

Alternator	Standard alternator: 250 amp alternator on 3.5L PFDI V6 and 3.5L EcoBoost® V6 engines Available dual alternator: 250 amps each, includes auxiliary fuse panel with high-spec interface connector; Included with ambulance prep packages, available on 3.5L EcoBoost® V6 engine only
Battery	Single battery – 70 amp-hr, 610 CCA, standard on 3.5L PFDI V6 and 3.5L EcoBoost® V6 engines Dual AGM batteries – 70 amp-hr each, available on 3.5L EcoBoost® V6 and 3.5L PFDI V6 engines

TRANSMISSIONS

Ten-speed SelectShift® Automatic Transmission

Configuration	Electronically controlled hydraulic 10-speed automatic overdrive with Selectable Drive Modes
First gear ratio	4.696:1
Second gear ratio	2.985:1
Third gear ratio	2.146:1
Fourth gear ratio	1.769:1
Fifth gear ratio	1.520:1
Sixth gear ratio	1.275:1
Seventh gear ratio	1.1
Eighth gear ratio	0.854:1
Ninth gear ratio	0.689:1
Tenth gear ratio	0.636:1
Reverse	-4.866:1

SUSPENSION

Front configuration	Front independent MacPherson strut suspension with stabilizer bar
Front shock absorber type	Gas-pressurized
Rear configuration	Solid rear axle, leaf springs
Rear shock absorber type	Gas-pressurized

STEERING

130-inch wheelbase

148-inch wheelbase

Type	Electric power-assisted	Electric power-assisted
Turning circle, curb-to-curb	43.5 feet	48.5 feet

BRAKES

Front

Rear

Type	Power anti-lock disc	Power anti-lock disc
Rotor diameter	12.1 inches outer/6.5 inches inner	12.1 inches outer/7.9 inches inner
Caliper configuration	Two calipers, 1.89 inches diameter	Single caliper, 2.13 inches diameter
Axle total swept area	163 square inches	133 square inches
Parking brake (type)	Rear brake integrated caliper, hand-operated mechanical or electric	Rear brake integrated caliper, hand-operated mechanical or electric

FUEL CAPACITY

Standard	25 gallons
Optional	31 gallons



SAFETY/CONTROL SYSTEMS

ABS/stability control	Four-Wheel Anti-Lock Brakes, AdvanceTrac® with RSC® (Roll Stability Control™), side-wind stabilization system
Airbags	Driver and passenger front airbags, driver and passenger front-seat mounted side airbags, and Safety Canopy® curtain airbags
Chassis safety	Tire Pressure Monitoring System (TPMS), SOS Post-Crash Alert System™

DRIVER ASSIST

Standard	Ford Co-Pilot360® • Auto High-Beam Headlamps, Lane Keeping System, Intersection Assist, Camera-Only Evasive Steering Assist, Pre-Collision Assist® with Automatic Emergency Braking (AEB), Post-Collision Braking, Rear View Camera (kit on Chassis/Cutaway), Rear Parking Sensors (only on Cargo/Passenger Van), Front Parking Sensors
Available	Ford Co-Pilot360® Assist 2.0 for Cargo and Passenger Van (Standard on XLT) and Ford Co-Pilot360® Assist+ for Chassis Cab/Cutaway • All of Ford Co-Pilot360® standard features plus: SiriusXM® with 360L, HD Radio™, Connected Navigation, front fog lamps, Adaptive Cruise Control, Blind Spot Information System (BLIS®) with Cross Traffic Alert, Short-Arm, Power Adjusting, Power Folding Heated Mirrors with Turn Signals • Cargo/Passenger only, also includes: 360-Degree Camera, Side Parking Sensors, Reverse Brake Assist • Chassis Cab/Cutaway only, also includes: Exit Warning, Rear Cross Traffic Braking, Blind Spot Assist, Rear Parking Sensors Kit

WHEELS

	Cargo Van	Passenger Van XL	Passenger Van XLT	Cutaway	Chassis Cab
16-inch silver-painted steel wheel; SRW With black hubcap (Standard front axle configurations only)	S	S	N/A	S	S
16-inch silver-painted steel wheel; SRW With silver hubcap and exposed lug nuts (Heavy-duty front axle configurations only)	S	S	S	S	S
16-inch silver-painted steel wheel w/ silver cover; SRW Included with Exterior Upgrade Package (Standard front axle configurations only)	0	0	S	0	0
16-inch black-painted aluminum-alloy wheel; SRW Available with Exterior Upgrade Package (Standard front axle configurations only)	0	0	0	0	0
16-inch silver-painted aluminum-alloy wheel; SRW Available with Exterior Upgrade Package (Standard front axle configurations only)	0	0	0	0	0
16-inch Sparkle Silver-painted alloy wheel; SRW Available with Exterior Upgrade Package (Heavy-duty front axle configurations only)	0	0	0	0	0
16-inch Matte Black-painted alloy wheel; SRW Available with Exterior Upgrade Package (Heavy-duty front axle configurations only)	0	0	0	0	0
16-inch heavy-duty steel wheel; DRW Silver-painted with silver hubcap and exposed lug nuts (Standard and heavy-duty front axle configurations)	S	S	S	S	S
16-inch heavy-duty forged aluminum wheel; DRW Available with Exterior Upgrade Package (Heavy-duty front axle configurations only)	0	0	0	0	0

HEADLIGHTS

Standard hi/low automatic on/off	Halogen
Available	Black High-Intensity Discharge (HID) – Standard on XLT
Optional fog lamps	Halogen



EXTERIOR DIMENSIONS

	Cargo Van					Passenger Van			
	REGULAR	LONG	LONG	LONG	EXTENDED	LONG	LONG	LONG	EXTENDED
Roof height	Low	Low	Medium	High	High	Low	Medium	High	High
Wheelbase (inches unless otherwise noted)	129.9	147.6	147.6	147.6	147.6/ —	147.6	147.6	147.6	147.6
Length (overall)	219.9	237.6	235.5	235.5	263.9/—	237.6	235.5	235.5	263.9
Height	82.2	82.9	101.3	109.6	110.4/ —	82.4	99.2	108.6	107.7
Width, excluding mirrors (SRW/DRW)	81.3	81.3	81.3	81.3	81.3/83.7	81.3	81.3	81.3	81.3
Width, including mirrors	97.4	97.4	97.4	97.4	97.4/ —	97.4	97.4	97.4	97.4
Width, mirrors folded	83.2	83.2	83.2	83.2	83.2/83.7	83.2	83.2	83.2	83.2
Front track (SRW/DRW)	68.2	68.2	68.2	68.2	68.2/68.5	68.2	68.2	68.2	68.2
Rear track (SRW/DRW)	68.6	68.6	68.6	68.6	68.6/65.7	68.6	68.6	68.6	68.6
Front overhang	40.3	40.3	40.3	40.3	40.3/ —	40.3	40.3	40.3	40.3
Rear overhang	49.7	49.7	47.6	47.6	76.0/ —	49.7	47.6	47.6	76.0
Load height (curb)	28.9	28.7	28.7	28.7	28.0/ —	28.8	28.8	28.8	27.8
Rear cargo door opening height	49.5	49.5	64.9	74.3	74.3/ —	46.9	62.8	72.2	72.2
Rear cargo door opening width	61.7	61.7	61.7	61.7	61.7/ —	59.8	59.8	59.8	59.8
Side cargo door opening height	49.6	49.6	63.0	63.0	63.0/ —	67.2	67.2	67.2	67.2
Side cargo door open. width (hinged)	51.2	51.2	51.2	51.2	51.2/ —	74.0	74.0	74.0	74.0
Side cargo door open. width (sliding)	51.2	51.2	51.2	51.2	51.2/ —	74.0	74.0	N/A	N/A

INTERIOR DIMENSIONS

	Cargo Van					Passenger Van			
	REGULAR	LONG	LONG	LONG	EXTENDED	LONG	LONG	LONG	EXTENDED
Roof height	Low	Low	Medium	High	High	Low	Medium	High	High
Head room – First row (inches unless noted)	40.8	40.8	52.0	56.6	56.6/ —	40.8	52.0	56.6	56.6
Head room – Second row (where applicable)	—	—	—	—	—	41.1	55.8	65.2	65.2
Head room – Third row (where applicable)	—	—	—	—	—	40.6	55.8	65.2	65.2
Head room – Fourth row (where applicable)	—	—	—	—	—	38.7	55.8	65.2	65.2
Head room – Fifth row (where applicable)	—	—	—	—	—	38.1	52.6	61.3	61.3
Leg room – First row (max)	41.3	41.3	41.3	41.3	41.3/ —	41.3	41.3	41.3	41.3
Leg room – Second row (where applicable)	—	—	—	—	—	33.7	33.7	33.7	33.7
Leg room – Third row (where applicable)	—	—	—	—	—	35.6	35.6	35.6	35.6
Leg room – Fourth row (where applicable)	—	—	—	—	—	35.6	35.6	35.6	35.6
Leg room – Fifth row (where applicable)	—	—	—	—	—	35.6	35.6	35.6	35.6
Hip room – First row	60.7	60.7	60.7	60.7	60.7/ —	60.7	60.7	60.7	60.7
Hip room – Second row (where applicable)	—	—	—	—	—	69.6	69.6	69.6	69.6
Hip room – Third row (where applicable)	—	—	—	—	—	67.3	67.3	67.3	67.3
Hip room – Fourth row (where applicable)	—	—	—	—	—	68.0	68.0	68.0	68.0
Hip room – Fifth row (where applicable)	—	—	—	—	—	68.0	68.0	68.0	68.0
Shoulder room – First row	67.9	67.9	67.9	67.9	67.9/ —	67.9	67.9	67.9	67.9
Shoulder room – Second row (where app.)	—	—	—	—	—	71.4	71.4	71.4	71.4
Shoulder room – Third row (where app.)	—	—	—	—	—	67.0	67.0	67.0	67.0
Shoulder room – Fourth row (where app.)	—	—	—	—	—	67.8	67.8	67.8	67.8
Shoulder room – Fifth row (where app.)	—	—	—	—	—	67.8	67.8	67.8	67.8
Cargo floor length (front)	126.0	143.7	143.7	143.7	172.2/ —	141.7	141.7	141.7	170.2
Cargo belt length (front)	115.9	133.6	133.6	133.6	162.0/—	132.8	132.8	132.8	161.3
Cargo length b'twn wheelhouse (SRW/DRW)	54.8	54.8	54.8	54.8	54.8/45.4	53.7	53.7	53.7	53.7
Cargo height (max)	56.9	56.9	72.0	81.5	81.5/ —	52.8	67.6	77.0	77.0



BASE CURB WEIGHT (LBS)

Length	Regular	Long	Long	Long	Extended
Roof height	Low	Low	Medium	High	High
Cargo Van 3.5L PFDI gas (RWD/AWD)	4,954/5,150	5,056/5,263	5,204/5,411	5,299/5,506	5,543/5,773 (SRW)
Cargo Van 3.5L EcoBoost® (RWD/AWD)	5,019/5,218	5,124/5,329	5,270/5,475	5,365/5,570	5,669/5,897 (SRW)
Passenger Van 3.5L PFDI gas (RWD/AWD)	N/A	6,051/6,258	6,186/6,393	6,325/6,532	N/A
Passenger Van EcoBoost (RWD/AWD)	N/A	6,116/6,320	6,249/6,453	6,391/6,596	6,958/7,186 (DRW)

CAPACITIES (CU. FT.)

Length	Regular	Long	Long	Long	Extended
Roof height	Low	Low	Medium	High	High
Cargo Van seating	2	2	2	2	2
Cargo Van cargo volume behind first row	246.7	277.7	357.1	404.3	487.3
Cargo Van maximum cargo volume (with front passenger seat removed)	280.9	311.9	400.5	453.4	536.4
Passenger Van seating	N/A	2, 12, 15	2, 12, 15	2, 12, 15	2, 12, 15
Passenger Van cargo volume behind first row (range)	N/A	223.5–256.4	303.1–336.1	349.6–382.6	425.4–461.9
Passenger Van cargo volume behind second row (range)	N/A	150.0–183.0	206.8–239.8	240.1–273.0	313.1
Passenger Van cargo volume behind third row (range)	N/A	91.5–124.5	133.9–166.9	157–190	230.0
Passenger Van cargo volume behind fourth row (range)	N/A	48.9–70.1	72.8–93.9	85.8–107.0	184.0
Passenger Van cargo volume behind fifth row	N/A	N/A	N/A	N/A	100.5

MAXIMUM PAYLOAD CAPABILITIES – CARGO VAN

Transit® Level	Engine	Roof Height	Length	Wheelbase (in)	RWD/AWD	GVWR (lbs) ²	Max Payload (lbs) ²
T-150	3.5L EcoBoost V6	Low	Regular	130	AWD	8,670	3,452
T-150	3.5L PFDI V6	Low	Regular	130	AWD	8,670	3,519
T-150	3.5L EcoBoost V6	Low	Regular	130	RWD	8,670	3,650
T-150	3.5L PFDI V6	Low	Regular	130	RWD	8,670	3,716
T-150	3.5L EcoBoost V6	Low	Regular	130	AWD	8,800	3,530
T-150	3.5L PFDI V6	Low	Regular	130	AWD	8,800	3,598
T-150	3.5L EcoBoost V6	Low	Regular	130	RWD	8,800	3,730
T-150	3.5L PFDI V6	Low	Regular	130	RWD	8,800	3,796
T-150	3.5L EcoBoost V6	Low	Long	148	AWD	8,670	3,342
T-150	3.5L PFDI V6	Low	Long	148	AWD	8,670	3,406
T-150	3.5L EcoBoost V6	Low	Long	148	RWD	8,670	3,546
T-150	3.5L PFDI V6	Low	Long	148	RWD	8,670	3,613
T-150	3.5L EcoBoost V6	Low	Long	148	AWD	8,800	3,419
T-150	3.5L PFDI V6	Low	Long	148	AWD	8,800	3,484
T-150	3.5L EcoBoost V6	Low	Long	148	RWD	8,800	3,625
T-150	3.5L PFDI V6	Low	Long	148	RWD	8,800	3,693

²Max payload varies based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.



MAXIMUM PAYLOAD CAPABILITIES – CARGO VAN (continued)

Transit Level	Engine	Roof Height	Length	Wheelbase (in)	RWD/AWD	GVWR (lbs) ²	Max Payload (lbs) ²
T-150	3.5L EcoBoost V6	Medium	Long	148	AWD	8,670	3,195
T-150	3.5L PFDI V6	Medium	Long	148	AWD	8,670	3,258
T-150	3.5L EcoBoost V6	Medium	Long	148	RWD	8,670	3,399
T-150	3.5L PFDI V6	Medium	Long	148	RWD	8,670	3,465
T-150	3.5L EcoBoost V6	Medium	Long	148	AWD	8,800	3,270
T-150	3.5L PFDI V6	Medium	Long	148	AWD	8,800	3,334
T-150	3.5L EcoBoost V6	Medium	Long	148	RWD	8,800	3,476
T-150	3.5L PFDI V6	Medium	Long	148	RWD	8,800	3,543
T-250	3.5L EcoBoost V6	Low	Regular	130	RWD	9,070	4,050
T-250	3.5L PFDI V6	Low	Regular	130	AWD	9,070	3,919
T-250	3.5L PFDI V6	Low	Regular	130	RWD	9,070	4,116
T-250	3.5L PFDI V6	Low	Regular	130	RWD	9,150	4,146
T-250	3.5L EcoBoost V6	Low	Regular	130	RWD	9,150	4,080
T-250	3.5L PFDI V6	Low	Regular	130	AWD	9,150	3,948
T-250	3.5L EcoBoost V6	Low	Regular	130	AWD	9,150	3,880
T-250	3.5L EcoBoost V6	Low	Long	148	AWD	9,070	3,741
T-250	3.5L EcoBoost V6	Low	Long	148	RWD	9,070	3,945
T-250	3.5L PFDI V6	Low	Long	148	AWD	9,070	3,806
T-250	3.5L PFDI V6	Low	Long	148	RWD	9,070	4,013
T-250	3.5L PFDI V6	Low	Long	148	RWD	9,150	4,043
T-250	3.5L EcoBoost V6	Low	Long	148	RWD	9,150	3,974
T-250	3.5L PFDI V6	Low	Long	148	AWD	9,150	3,834
T-250	3.5L EcoBoost V6	Low	Long	148	AWD	9,150	3,768
T-250	3.5L EcoBoost V6	Medium	Long	148	AWD	9,070	3,595
T-250	3.5L EcoBoost V6	Medium	Long	148	RWD	9,070	3,799
T-250	3.5L PFDI V6	Medium	Long	148	AWD	9,070	3,658
T-250	3.5L PFDI V6	Medium	Long	148	RWD	9,070	3,865
T-250	3.5L PFDI V6	Medium	Long	148	RWD	9,150	3,893
T-250	3.5L EcoBoost V6	Medium	Long	148	RWD	9,150	3,826
T-250	3.5L PFDI V6	Medium	Long	148	AWD	9,150	3,684
T-250	3.5L EcoBoost V6	Medium	Long	148	AWD	9,150	3,620
T-250	3.5L EcoBoost V6	High	Long	148	AWD	9,070	3,500
T-250	3.5L EcoBoost V6	High	Long	148	RWD	9,070	3,704
T-250	3.5L PFDI V6	High	Long	148	AWD	9,070	3,563
T-250	3.5L PFDI V6	High	Long	148	RWD	9,070	3,770
T-250	3.5L PFDI V6	High	Long	148	RWD	9,150	3,797
T-250	3.5L EcoBoost V6	High	Long	148	RWD	9,150	3,731
T-250	3.5L PFDI V6	High	Long	148	AWD	9,150	3,588
T-250	3.5L EcoBoost V6	High	Long	148	AWD	9,150	3,524

²Max payload varies based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.



MAXIMUM PAYLOAD CAPABILITIES – CARGO VAN (continued)

Transit Level	Engine	Roof Height	Length	Wheelbase (in)	RWD/AWD	GVWR (lbs) ²	Max Payload (lbs) ²
T-250	3.5L EcoBoost V6	High	Long-EL	148	AWD	9,070	3,298
T-250	3.5L EcoBoost V6	High	Long-EL	148	RWD	9,070	3,502
T-250	3.5L PFDI V6	High	Long-EL	148	AWD	9,070	3,360
T-250	3.5L PFDI V6	High	Long-EL	148	RWD	9,070	3,567
T-250	3.5L PFDI V6	High	Long-EL	148	RWD	9,150	3,592
T-250	3.5L EcoBoost V6	High	Long-EL	148	RWD	9,150	3,527
T-250	3.5L PFDI V6	High	Long-EL	148	AWD	9,150	3,383
T-250	3.5L EcoBoost V6	High	Long-EL	148	AWD	9,150	3,320
T-350	3.5L EcoBoost V6	Low	Regular	130	AWD	9,500	4,230
T-350	3.5L EcoBoost V6	Low	Regular	130	RWD	9,500	4,430
T-350	3.5L PFDI V6	Low	Regular	130	AWD	9,500	4,298
T-350	3.5L PFDI V6	Low	Regular	130	RWD	9,500	4,496
T-350	3.5L EcoBoost V6	Low	Long	148	AWD	9,500	4,127
T-350	3.5L EcoBoost V6	Low	Long	148	RWD	9,500	4,342
T-350	3.5L PFDI V6	Low	Long	148	AWD	9,500	4,184
T-350	3.5L PFDI V6	Low	Long	148	RWD	9,500	4,393
T-350	3.5L EcoBoost V6	Medium	Long	148	AWD	9,500	3,970
T-350	3.5L EcoBoost V6	Medium	Long	148	RWD	9,500	4,185
T-350	3.5L PFDI V6	Medium	Long	148	AWD	9,500	4,034
T-350	3.5L PFDI V6	Medium	Long	148	RWD	9,500	4,243
T-350	3.5L EcoBoost V6	High	Long	148	AWD	9,500	3,880
T-350	3.5L EcoBoost V6	High	Long	148	RWD	9,500	4,095
T-350	3.5L PFDI V6	High	Long	148	AWD	9,500	3,938
T-350	3.5L PFDI V6	High	Long	148	RWD	9,500	4,147
T-350	3.5L EcoBoost V6	High	Long-EL	148	AWD	9,500	3,670
T-350	3.5L EcoBoost V6	High	Long-EL	148	RWD	9,500	3,877
T-350	3.5L PFDI V6	High	Long-EL	148	AWD	9,500	3,733
T-350	3.5L PFDI V6	High	Long-EL	148	RWD	9,500	3,942
T-350HD SRW	3.5L EcoBoost V6	Low	Long	148	AWD	9,950	4,577
T-350HD SRW	3.5L EcoBoost V6	Low	Long	148	RWD	9,950	4,792
T-350HD SRW	3.5L PFDI V6	Low	Long	148	AWD	9,950	4,634
T-350HD SRW	3.5L PFDI V6	Low	Long	148	RWD	9,950	4,843
T-350HD SRW	3.5L EcoBoost V6	Medium	Long	148	AWD	9,950	4,420
T-350HD SRW	3.5L EcoBoost V6	Medium	Long	148	RWD	9,950	4,635
T-350HD SRW	3.5L PFDI V6	Medium	Long	148	AWD	9,950	4,484
T-350HD SRW	3.5L PFDI V6	Medium	Long	148	RWD	9,950	4,693
T-350HD SRW	3.5L EcoBoost V6	High	Long	148	AWD	9,950	4,330
T-350HD SRW	3.5L EcoBoost V6	High	Long	148	RWD	9,950	4,545
T-350HD SRW	3.5L PFDI V6	High	Long	148	AWD	9,950	4,388
T-350HD SRW	3.5L PFDI V6	High	Long	148	RWD	9,950	4,597

²Max payload varies based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.



MAXIMUM PAYLOAD CAPABILITIES – CARGO VAN (continued)

Transit Level	Engine	Roof Height	Length	Wheelbase (in)	RWD/AWD	GVWR (lbs) ²	Max Payload (lbs) ²
T-350HD SRW	3.5L EcoBoost V6	High	Long	148	AWD	9,950	3,994
T-350HD SRW	3.5L EcoBoost V6	High	Long	148	RWD	9,950	4,223
T-350HD SRW	3.5L PFDI V6	High	Long	148	AWD	9,950	4,118
T-350HD SRW	3.5L PFDI V6	High	Long	148	RWD	9,950	4,351
T-350HD DRW	3.5L EcoBoost V6	High	Long-EL	148	AWD	9,950	3,884
T-350HD DRW	3.5L EcoBoost V6	High	Long-EL	148	RWD	9,950	4,113
T-350HD DRW	3.5L PFDI V6	High	Long-EL	148	AWD	9,950	3,948
T-350HD DRW	3.5L PFDI V6	High	Long-EL	148	RWD	9,950	4,181
T-350HD DRW	3.5L EcoBoost V6	High	Long-EL	148	AWD	11,000	4,873
T-350HD DRW	3.5L EcoBoost V6	High	Long-EL	148	RWD	11,000	5,103

MAXIMUM PAYLOAD CAPABILITIES – PASSENGER VAN

Transit Level	Engine	Seating	Roof Height	Length	Wheelbase (inches)	RWD/AWD	GVWR (lbs) ²	Max Payload (lbs) ²
T-350	3.5L EcoBoost V6	12	Low	Long	148	AWD	9,250	2,929
T-350	3.5L EcoBoost V6	12	Low	Long	148	RWD	9,250	3,134
T-350	3.5L PFDI V6	12	Low	Long	148	AWD	9,250	2,992
T-350	3.5L PFDI V6	12	Low	Long	148	RWD	9,250	3,199
T-350	3.5L PFDI V6	15	Low	Long	148	RWD	9,400	3,288
T-350	3.5L EcoBoost V6	15	Low	Long	148	RWD	9,400	3,222
T-350	3.5L EcoBoost V6	12	Low	Long	148	AWD	9,400	3,016
T-350	3.5L PFDI V6	12	Low	Long	148	AWD	9,400	3,079
T-350	3.5L EcoBoost V6	15	Low	Long	148	AWD	9,550	3,166
T-350	3.5L PFDI V6	15	Low	Long	148	AWD	9,550	3,229
T-350	3.5L EcoBoost V6	12	Medium	Long	148	AWD	9,250	2,800
T-350	3.5L EcoBoost V6	12	Medium	Long	148	RWD	9,250	3,004
T-350	3.5L PFDI V6	12	Medium	Long	148	AWD	9,250	2,863
T-350	3.5L PFDI V6	12	Medium	Long	148	RWD	9,250	3,070
T-350	3.5L EcoBoost V6	15	Medium	Long	148	RWD	9,400	3,088
T-350	3.5L PFDI V6	15	Medium	Long	148	RWD	9,400	3,077
T-350	3.5L PFDI V6	12	Medium	Long	148	AWD	9,400	2,949
T-350	3.5L EcoBoost V6	12	Medium	Long	148	AWD	9,400	2,885
T-350	3.5L PFDI V6	15	Medium	Long	148	RWD	9,500	3,177
T-350	3.5L EcoBoost V6	15	Medium	Long	148	RWD	9,500	3,188
T-350	3.5L EcoBoost V6	15	Medium	Long	148	AWD	9,550	3,032
T-350	3.5L PFDI V6	15	Medium	Long	148	AWD	9,550	3,092
T-350HD DRW	3.5L EcoBoost V6	15	High	Long-EL	148	RWD	10100	3071
T-350HD DRW	3.5L EcoBoost V6	15	High	Long-EL	148	AWD	10,100	3,071

²Max payload varies based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.



MAXIMUM TOWING CAPABILITIES – CONVENTIONAL TOWING

Model	Engine	Wheelbase (inches)	Axle Ratio	GCWR (lbs)	Max Towing RWD (lbs) ³	Max Towing AWD (lbs) ³
Cargo Van	3.5L PFDI V6	129.9	3.73/4.10	10,800/12,000	5,300/6,400	5,000/6,100
Cargo Van	3.5L PFDI V6	147.6	3.73/4.10	10,800/12,000	5,299/6,300	5,000/6,100
Passenger Van	3.5L PFDI V6	147.6	3.73/4.10	10,800/11,200	4,200/4,500	4,000/4,300
Cargo Van	3.5L EcoBoost V6	129.9	3.73	12,600	6,900	6,700
Cargo Van	3.5L EcoBoost V6	147.6	3.73	12,600	6,800	6,600
Passenger Van	3.5L EcoBoost V6	147.6	3.73	11,200	4,400	4,200

³Maximum towing capacities for properly equipped base vehicles with required equipment. Do not exceed trailer weight of 5,000 lbs when towing with bumper only. When properly equipped. Max towing varies based on cargo, vehicle configuration, accessories, and number of passengers.

WARRANTY

Bumper-to-Bumper	3 years/36,000 miles
Powertrain	5 years/60,000 miles
Safety Restraint System	5 years/60,000 miles
Corrosion (perforation only)	5 years/unlimited miles
Roadside Assistance Program	5 years/60,000 miles

